

REFERENCIAS

- Appel, C.A., y J.D. Bredehoeft, 1976. Status of ground water modeling in the U.S. Geological Survey. U.S. Geological Survey Circular 737. 9 pp.
- Bachmat, Y., B. Andrews, D. Holtz, y S. Sebastian, 1978. Utilization of numerical Groundwater Models for water resources management. U.S. Environ. Prot. Agency Report EPA-600/8-78-012. 178 pp.
- Bachmat, Y., J. Bredehoeft, B. Andrews, D. Holtz y S. Sebastian, 1980. Groundwater Management: The use of numerical modelos. American Geo. Union. Water Resources Monograph 5. 127 pp.
- Bear, J., D. Zaslavsky y S. Irmy, 1968. "Physical principals of water percolation and Seepage", UNESCO Paris, 465 pp.
- Bear, J., 1979. Hydraulics of Groundwater. Technion-Israel Institute of Technology 536 pp McGraw-Hill. New York, N.Y.
- Boulton, N.S., 1963. Analysis of data for non-equilibrium pumping tests allowing for delayed yield from storage. Proc. Inst. Civ. Engrs. (Londres), 26, 469-482 (y discusión posterior; pags

- Boulton, N.S., 1942. The steady Flow of groundwater to a pumped well in the vicinity of a river. The Philosophical Magazine v. 7:34-50.
- Bower, H. 1978. Ground Water Hydrology. McGraw-Hill Series in Water Resources and Environmental Engineering.
- Cooley, R.L., 1971. A finite difference method for variable saturated porous media: Application to a single pumping well. Water Resources Research. v.7., no. 6 pp. 1607-1625
- Cooper, H.H. y C.E. Jacob, 1946. A generalized graphical method for evaluating formation constants and summarizing well field history. Am. Geophys. Union Trans. 27:526-534.
- Custodio, M. y M.R. Llamas, 1976. Hidrología Subterránea. Tomos I y II. Ed. Omega. Barcelona, España.
- Chow, V.T., 1962. Hydrologic Determination of Waterway Areas for the desing of drainage structures. Small drainage basins. Univ. Ill. Eng. Expt. Sta. Bull 462
- De Wiest, R.J.M., 1966. On the storage coefficient and the equations of Ground-Water Flow. Jour. Geophys. Research, v. 71, no 4, Febrero 15.
- Drake, R.L., F.J. Molz, I. Remson, y A.A. Fungaroli, 1969. "Similarity aproximation for radial subsurface flow problem", Water Resources Research, vol. 5 673-684.
- Forsythe, G.E. y W.R. Wasow, 1960. Finite-Difference Methods for partial differential equations: New York, John Wiley and Sons.
- F.S.A.R., 1979. Final Safety Analysis Report. Sección 2.4 y 2.5 Hydrologic Engineering y Geology. Tomo II capítulo 2. CFE/PNLV.
- INFORME AMBIENTAL, 1980. Meteorología, sección 1.3 Ingeniería Ambiental PNLV/CFE Tomos I, II, y III

- INFORME AMBIENTAL, 1980. Hidrología, sección 1.4. Ingeniería Ambiental PNLV/CFE tomos I,II y III
- Jensen, M.E. y R.J. Hanks, 1967. "Nonsteady-state drainage from porous media", J. Irr.Dr. Div. ASCE, vol. 93, no. IR3 209-231.
- Jeppson, R.W. y R.W. Nelson, 1970. "Inverse formulation and finite-difference solution to partially saturated seepage from canals". Soil Sci. Soc. Am. Proc., vol 34, 9-14.
- Hantush, M.S. 1965. Wells near streams with semipervious beds. Journal Geophysical Research v. 70(12)
- Karplus, W.J., 1958. Analog simulation. McGraw-Hill Book Co., Inc., New York, N.Y.
- Kruseman, G.P. y N.A. DeRidder, 1975. Analysis and Evaluation of pumping test data. International Institute for Land Reclamation and Improvement, Holanda Bulletin 11s pp 212
- Mercer, J.W. y C.R. Faust, 1980. Ground-Water Modeling: Recent Developments. GROUNDWATER vol. 18, no.6, pp. 569-577
- Mercer, J.W. y C.R. Faust, 1981. Ground Water Modeling. I.G.W.M.C. y N.W.W.A. pag. 1-8.
- Moore, J.E., 1979. Contribution of groundwater modeling to planning. Journal of Hydrology. v. 43(oct), pp. 121-128.
- Mooser, H.F. y S. Soto, 1978. Geology around Laguna Verde. FSAR section 2.5 Geology. CFE. M2.5.3
- Narasimhan, T.N. y P.A. Whitherspoon, 1976. An integrated finite difference method for analyzing fluid flow in porous media. Water Resources Res. v 12, no.1 pp 57-64
- Peaceman, D.W y H.H. Rachford jr., 1955. The numerical solution of parabolic and elliptic differential equations. Journal Society of Industrial and Applied Mathematics v. 3:28-41.

- Pinder, G.F. y J.D. Bredehoeft, 1968. Application of the digital computer for aquifer evaluation. Water Resources Research v. 4 (5).
- Prickett, T.A. y C.G. Lonquist, 1971. Selected digital computer techniques for groundwater resource evaluation. Illinois State Water Survey Bull. 55, Urbana. 62 pag.
- Prickett, T.A., 1979. Ground-Water computer models-state of the art. Ground Water v. 17, no 2, pag 167-173.
- Prickett, T.A. 1965. Type-curve solution to aquifer tests under water table conditions. Groundwater 3, 3:5-14.
- Residencia de Estudios Geológicos-Zona Golfo. Julio 1981. Pruebas de permeabilidad "Lefranc" en el valle "El Viejón". CFE P.N. Laguna Verde. 10 p.
- Richtmeyer, R.D. y K.W. Morton, 1967. Difference Methods for initial value problems. New York Intersciences.
- Rivera, A., 1982. Informe sobre pruebas de bombeo en los pozos A, D y E del Proyecto Nucleoeléctrico Laguna Verde. CFE-Ingeniería Ambiental.
- Rivera, A. y R.E. Favela, 1982. Determinación de la Avenida Máxima Probable (AMP) en las cuencas de los ríos Barranca Hernández y El Viejón. DIA PNLV/CFE. 38 pag.
- Rivera, A., 1982. Informe sobre los pozos 4 (D) y 5 (E) que abastecen a la PNLV. CFE/PNLV- Ingeniería Ambiental.
- Rivera, A., Septiembre 1983. Anteproyecto de localización y diseño preliminar del pozo de agua no. 6 para la etapa de operación de la PNLV. CFE-Ingeniería Ambiental. 34 pag.
- Rivera, A., O. Calzada, M. Gonzáles, R.E. Favela y M.A. Valdovinos, 1984. Informe sobre pruebas de bombeo realizadas en los pozos A,B y C del proyecto nucleoeléctrico Laguna Verde en Abril de 1984. CFE-Ingeniería Ambiental. 38 pag.

- Sahni, B.M. y H.B.S. Seth, 1979. Determination of storage coefficient without observation wells. Ponencia presentada en la III Conferencia Internacional sobre Recursos Hidráulicos, Ciudad de México. Pags 2648-2656.
- S.A.R.H., 1977. "Boletín Hidráulico No. 56". Secretaria de Recursos Hidráulicos S.A.R.H.
- Saulýev, V.K., 1964. Intergration of equations of parabolic type by the method of nets. G.J. Tee, Trans: New York, MacMillan.
- Smith, G.D., 1965. Numerical solution of partial differential equations. New York, Oxford Univ. Press.
- Soliman, M.M. 1972. "Determination of some hydrological factors with a well recorder", Proceedings Second International Symposium in Hydrology, Fort Collins, Colorado, USA; pp 74-79
- Theis, C.V., 1935. The relation between the lowering of the piezometric surface and the rate and duration of discharge of a well using groundwater storage: Trans. Am. Geophys. Union, v. 16 pp 519-524
- Thomas, R.G., 1973. Ground Water Models. Irrigation and drainage paper 21, Food and Agriculture Organization of the United Nations, Rome. 192 pp.
- Trescott, P.C., G.F. Pinder y S.P. Larson, 1976. Finite-difference model for aquifer simulation in two dimensions with results of numerical experiments. U.S. Geological Survey. Technics of Water Resources Investigations. Book 7, chap. C1, 116 pag.
- Tyson, H.N. y E.M. Weber, 1964. Groundwater management for the nation s future- computer simulation of ground water basins. J. Hydraul. Div. Amer. Soc. Civil Eng. v. 90, HY4, pp 59-77.

